

HEADER CONTROL VALVES

HUSCO
INTERNATIONAL
control focused - technology driven

HUSCO offers control valves for combine harvester header control. The header control valves include the ability to provide position, tilt, transport, and ground pressure control.



FEATURES & SPECIFICATIONS

- Flow rate: up to 120 lpm
- Operating pressure: 200 bar
- Temperature range: -40°C to 105°C

OPTIONS

- Load holding leakage: less than 1 ccm at 100 bar
- Header tilt, position, transport, and ground pressure control.
- Custom designs to incorporate other control functions
- Can be used with open or closed center pump systems

e-mail: sales@huscointl.com website: www.huscointl.com

World Headquarters

HUSCO International, Inc.
2239 Pewaukee Road
Waukesha, WI 53188
Phone: 1-262-513-4200
Fax: 1-262-513-4240

European Headquarters

HUSCO International, Ltd.
6 Rivington Road
Whitehouse Industrial
Estate Runcorn, Cheshire,
England WA7 3DT
Phone: (44)-1928-701888
Fax: (44)-1928-710813

India Headquarters

HUSCO Hydraulics Private Ltd.
Plot A4 - Talegaon Floriculture
Ind. Estate - MIDC
Village - Navlakh Umbre,
Talegaon, Puna 410507, India
Phone: (91)-211-4305327

Pacific Rim Headquarters

HUSCO Kayaba Hydraulics
(Shanghai) Ltd.
No. 235 Jiangtian Road East
Song Jiang Industrial Zone
Shanghai, 201600
P.R. China
Phone: (86)-21-5774-6468
Fax: (86)-21-3774-0186

HUSCO Brazil

Rua Jaragua 397 sala 702
Porto Alegre RS 90-450-140
Brazil
Phone: (55)-51-3388-4367
Fax: (55)-51-3321-4291