

HUSCO offers custom and standard valves for control of tractor hitches. These valves have been carefully designed to ensure optimal control by OEM software or the optional HUSCO Hitch with EZ-Select® electronic control hardware. The hitch valves can be stand-alone or can be incorporated into a sectional valve stack for control of other functions. The HUSCO VFH900 is a standard stand-alone hitch valve and is ideal for tractor applications below 100 HP.



FEATURES & SPECIFICATIONS

- Flow rate:
 - In valve stack: 120 lpm
 - Stand-alone VFH900: 90 lpm
- Operating pressure: 200 bar
- Temperature range: -40°C to 105°C

OPTIONS

- Stand-alone valve
- Integration into a sectional valve stack
- Load holding leakage: less than 1 ccm at 100 bar
- Custom designs to incorporate other control functions
- Can be used with open or closed center pump systems

e-mail: sales@huscointl.com website: www.huscointl.com

World Headquarters

HUSCO International, Inc.
2239 Pewaukee Road
Waukesha, WI 53188
Phone: 1-262-513-4200
Fax: 1-262-513-4240

European Headquarters

HUSCO International, Ltd.
6 Rivington Road
Whitehouse Industrial
Estate Runcorn, Cheshire,
England WA7 3DT
Phone: (44)-1928-701888
Fax: (44)-1928-710813

India Headquarters

HUSCO Hydraulics Private Ltd.
Plot A4 - Talegaon Floriculture
Ind. Estate - MIDC
Village - Navlakh Umbre,
Talegaon, Puna 410507, India
Phone: (91)-211-4305327

Pacific Rim Headquarters

HUSCO Kayaba Hydraulics
(Shanghai) Ltd.
No. 235 Jiangtian Road East
Song Jiang Industrial Zone
Shanghai, 201600
P.R. China
Phone: (86)-21-5774-6468
Fax: (86)-21-3774-0186

HUSCO Brazil

Rua Jaragua 397 sala 702
Porto Alegre RS 90-450-140
Brazil
Phone: (55)-51-3388-4367
Fax: (55)-51-3321-4291